

VHB2F

Motorized butterfly valves

Product features

DN25 - DN200

Kvs: 52 - 2852 m³/h

Medium: water -10 - 110 °C

U_v: AC 24 Volt or AC 230 Volt

Y: On/Off

Valve body: cast iron GGG-40 EN-JS1030

IP54

Types

Butterfly valves

Type	DN [mm]	Kvs [m ³ /h]	PFA [bar]
VHB2F025	25	52	16

BELPARTS Group NV

Wingepart 4
3110 Rotselaar
Belgium

T +32 (0)16 29 93 00

E info@belparts.com

belparts.com

1 / 4

All rights reserved © 2026 BELPARTS Group NV
Subject to modifications without prior notice.

Type	DN [mm]	Kvs [m³/h]	PFA [bar]
VHB2F032	32	72	16
VHB2F040	40	126	16
VHB2F050	50	124	16
VHB2F065	65	243	16
VHB2F080	80	397	16
VHB2F100	100	723	16
VHB2F125	125	1083	16
VHB2F150	150	1591	16
VHB2F200	200	2852	16

PFA: Maximum permissible medium pressure

Actuators (motorsets)

Type	U _v	Running time [s]	Torque [Nm]	Power [VA]
M130.4S	AC 24 V	130	35	6,5
M140.4S	AC 24 V	10	50	55
M180.4S	AC 24 V	130	80	26
M130.2S	AC 230 V	130	35	6,5
M140.2S	AC 230 V	10	50	55

Type	U _v	Running time [s]	Torque [Nm]	Power [VA]
M180.2S	AC 230 V	130	80	26

S2: With 2 integrated auxiliary switches (SPDT)

Specifications

Butterfly valves

DN25 - DN200

Kvs: 52 - 2852 m³/h

Medium: water -10 - 110 °C

Centering lugs

Valve body: cast iron GGG-40 EN-JS1030

Butterfly: Nylon 11 coating (> DN50)

Flanged connection PN6/10/16 with centering lug

Liner: EPDM

Actuators

U_v: AC 24 Volt or AC 230 Volt

Y: On/Off

Rotation angle: 90°

Running time: 10 s or 130 s

Manual override

Overload protected

IP54

Questions or request a quote for VHB2F?

Our experts can help you with technical questions, product selection and provide a quotation for your project.

Ask a questionRequest a quote



+32 (0)16 29 93 00