NG2P

2-port terminal control valves PN16

Product features

DN15, DN20 and DN25 (straight)
Medium: water 2 – 95 °C (VDI 2035)

Kvs: adjustable [1)]
Brass
Threaded
Flat connections ISO 228-1

Types

Type	DN [inch]	Kvs [m³/h]	In	Out
NG2P15A	½″	1,6 [1)]	G½″	G½″
NG2P15B	½″	1,0 [1)]	G½″	G½″

BELPARTS Group NV
Wingepart 4
3110 Rotselaar
Belgium

T +32 (0)16 29 93 00
E info@belparts.com

belparts.com

All rights reserved © 2026 BELPARTS Group NV
Subject to modifications without prior notice.

Type	DN [inch]	Kvs [m³/h]	In	Out
NG2P15C	½″	0,63 [1]	G½″	G½″
NG2P20A	¾″	3,5 [1]	G¾″	G¾″
NG2P20B	¾″	2,5 [1]	G¾″	G¾″
NG2P25A	1″	4,5 [1]	G1″	G1″

[1] Adjustable Kvs; see specifications

Specifications

Adjustable Kvs settings [m³/h]
NG2P15A: 0,2 – 0,63 – 1,0 – 1,3 – 1,5 – 1,6
NG2P15B: 0,2 – 0,3 – 0,4 – 0,63 – 0,85 – 1,0
NG2P15C: 0,2 – 0,4 – 0,5 – 0,55 – 0,6 – 0,63
NG2P20A: 1,0 – 1,9 – 2,5 – 2,9 – 3,1 – 3,5
NG2P20B: 0,3 – 1,1 – 1,9 – 2,2 – 2,4 – 2,5
NG2P25A: 1,0 – 1,9 – 3,0 – 3,9 – 4,2 – 4,5

Questions or request a quote for NG2P?

Our experts can help you with technical questions, product selection and provide a quotation for your project.

Ask a questionRequest a quote

BELPARTS Group NV
Wingepart 4
3110 Rotselaar
Belgium

T +32 (0)16 29 93 00
E info@belparts.com

belparts.com

All rights reserved © 2026 BELPARTS Group NV
Subject to modifications without prior notice.

+32 (0)16 29 93 00

BELPARTS Group NV
Wingepart 4
3110 Rotselaar
Belgium

T +32 (0)16 29 93 00
E info@belparts.com

belparts.com

All rights reserved © 2026 BELPARTS Group NV
Subject to modifications without prior notice.